
Optional Accessories

MOUNT







55-82mm



New Light-Stant Mount



15mm Rail Mount for R300 SE

62-82mm

SHAPING

Lens Adapter Ring 58-82mm

POWER













AC Adapter 5m Cable



for RS-1 Softbox

for R300 SE

Power Cable D-tap to DC - 0.5m



To prevent damaging the lens, when lens mounted don't use a NP-F battery to power the light, but use an external power source through the DC connector.



Quick Start Guide



R300 SE

LED Ring Light

- **Getting Started**
- **Functions**

What's in the box?



R300 SE



Lens Mount







Lens Adapter Ring x 3 67-82mm / 72-82mm / 77-82mm



Base Case for R300

Steenovenweg 5, 5708HN Helmond, The Netherlands TM & © F&V All rights reserved.

1 Getting Started

Mounting



2 Power

Two power options

- ① NP-F Li-ion battery
- ② DC Φ2.5 10-18V

3 Let's do this!

Turn the light ON

<I> when powering through DC Jack <II> when using NP-F batteries



2 Functions



Temperaturan Temperaturan Temperaturan

R300 5E

R300S 5E

- **1** Adjust the Intensity
 Use <Intensity> knob to adjust the intensity
- * Adjust the Color Temperature (only the bi-color version)
 Use <Color Temperature> knob to adjust the color temperature