

DHL42

42" Full-HD LCD Monitor



Features :

- Industrial level DID LCD panel, suitable for extensive 7x24 continuous works
- High fidelity digital processing, brilliant and vivid video
- 5.8ms fast response time, no picture ghosting
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Infrared, RS232 double mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan



Technical Specification

Model

Model	DHL42
-------	-------

System

Diagonal	42"(16:9)
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance (Standard)	700 cd/ m ²
Contrast	1000:1
Angle of view	178°/178°(vertical/horizontal)
Response time	5.8ms

Signals

Input	standard	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1
	optional	Audio×1
Output	Standard	CVBS(BNC)×2, RS232×1
	optional	DP×1

General

Consumption (Standard)	65W
Consumption (Standby)	≤1W

Power Supply	AC100~240V (+/-10%),50/60 Hz
Weight	17kg
Dimensions(no base)	1004.00×598.00×48.20mm
Work Environment	Temperature:0 C~50 C
	Humidity:20%~90%

Accessory

Standard	VGA cable, power cable
Optional	Pedestal, hanging bracket

Dimensions(mm)

